

All in overview.

Lubricants for cars and trucks.



Contents page

Engine Oils		page 4-11	
Engine Oils for Passenger Cars	page	Engine Oils for Heavy Trucks	page
<ul style="list-style-type: none"> • Aral SuperTronic SAE 0W-40 • Aral SuperTronic E SAE 0W-30 • Aral SuperTronic G SAE 0W-30 • Aral SuperTronic LongLife III SAE 5W-30 • Aral HighTronic C SAE 5W-30 • Aral HighTronic F SAE 5W-30 • Aral HighTronic G SAE 5W-30 • Aral HighTronic J SAE 5W-30 • Aral HighTronic M SAE 5W-30 • Aral HighTronic R SAE 5W-30 • Aral HighTronic SAE 5W-40 • Aral HighTronic M SAE 5W-40 • Aral BlueTronic SAE 10W-40 • Aral Tronic SAE 15W-40 	<p>4</p> <p>5</p> <p>6</p> <p>7</p>	<ul style="list-style-type: none"> • Aral SuperTurboral SAE 5W-30 • Aral SuperTurboral LA SAE 5W-30 • Aral MegaTurboral LA SAE 10W-40 • Aral MegaTurboral S SAE 10W-40 • Aral MegaTurboral SAE 10W-40 • Aral MegaTurboral VR SAE 10W-40 • Aral ExtraTurboral SAE 10W-40 • Aral PlusTurboral SAE 15W-40 • Aral MultiTurboral SAE 15W-40 • Aral BasicTurboral SAE 10W, 20W-20, 30, 40, 50 • Aral Kowal CNG SAE 15W-40 • Aral SuperTraktoral SAE 10W-40 	<p>8</p> <p>9</p> <p>10</p> <p>10-11</p>
Transmission Fluids for Passenger Cars and Heavy Trucks		page 12-17	
ATF	page	Manual	page
<ul style="list-style-type: none"> • Aral Getriebeöl SGF 84 • Aral Getriebeöl ATF 22 • Aral Getriebeöl ATF 55 • Aral Getriebeöl ATF M 12 • Aral Getriebeöl ATF J • Aral Getriebeöl ATF E-S • Aral Getriebeöl ATF LD 	<p>12</p> <p>13</p>	<ul style="list-style-type: none"> • Aral Getriebeöle EP SAE 80W, 85W-90, 85W-140 • Aral Getriebeöle EP SYNTH SAE 75W-90 • Aral Getriebeöl SNS SAE 75W-80 • Aral Getriebeöl SNS-A SAE 75W-85 • Aral Getriebeöl SNS-B SAE 75W-80 • Aral Getriebeöl SNS-AT SAE 75W-90 • Aral Fluid HGS SAE 80W • Aral Fluid T0-4 SAE 10W, 30, 50 	<p>13</p> <p>14</p> <p>15</p>
Axle	page	Manual and Axle	page
<ul style="list-style-type: none"> • Aral Getriebeöl HYP LS SAE 85W-90 • Aral Getriebeöle HYP 80W, SAE 85W-90, 85W-140 • Aral Getriebeöl SNA-D SAE 80W-90 • Aral Getriebeöl HYP SYNTH SAE 75W-90 • Aral Getriebeöl BS SAE 75W-90 • Aral Getriebeöl BS-LSX SAE 75W-140 • Aral Getriebeöl SNA-C SAE 75W-90 	<p>15</p> <p>16</p>	<ul style="list-style-type: none"> • Aral Getriebeöl EP Plus SAE 80W-90 • Aral Getriebeöl SNA-B SAE 80W-140 • Aral Getriebeöl SNA-E SAE 75W-90 • Aral Getriebeöl HYP SC SAE 85W-140 	<p>17</p>
Specialities / Greases		page 18-19	
Antifreeze	page	Brakefluids	page
<ul style="list-style-type: none"> • Aral Antifreeze Silikatfrei • Aral Antifreeze Extra 	<p>18</p>	<ul style="list-style-type: none"> • Aral Bremsflüssigkeit HS DOT 4 • Aral Bremsflüssigkeit HS DOT 4 Super 	<p>18</p>
Additional Products	page	Greases	page
<ul style="list-style-type: none"> • Aral Kipper-Hydrauliköl • Aral LHM + 	<p>18</p>	<ul style="list-style-type: none"> • Aral Mehrzweckfett • Aral Mehrzweckfett F • Aral Langzeitfett H • Aral Radlagerfett • Aral Fließfett N 	<p>19</p>

Engine Oils

Passenger Cars



Article No. Aral	Capacity	Container	
Engine Oils for Passenger Cars			
Aral SuperTronic SAE 0W-40		ACEA C2, C3 • API SM/ CF • MB 229.31/ 229.51 • BMW Longlife-04 • Fiat 9.55535-S2 • Porsche A40	
10456	lose Ware		<p>Fully synthetic high performance engine oil for gasoline and diesel engines with and without diesel particle filters. Based on 'Aral Synthese Technologie'.</p> <ul style="list-style-type: none"> • Universally applicable with an extensive approval profile • 'Aral Low SAPS-Technologie' maximizes diesel particle filter lifespan • Safety for the engine at extended drain intervals • Lower fuel consumption of approximately 3 % and improved emissions performance • Meets ACEA 2007 A3/B3, A3/B4 performance levels
10450	205 Ltr.	Leihfass	
10451	60 Ltr.	Garagenfass	
10452	20 Ltr.	Kanister	
20459	4 Ltr.	Kanister	
20458	1 Ltr.	Dose	
Aral SuperTronic E SAE 0W-30		ACEA A5/B5 • API SL • ILSAC GF-2	
10506	lose Ware		<p>High performance engine oil with 'Aral Synthese Technologie'.</p> <ul style="list-style-type: none"> • For gasoline and diesel passenger cars from for example Volvo, Honda and Renault, needing engine oils according to ACEA A5, B5 • For extended drain intervals with certain Volvo cars
10500	205 Ltr.	Leihfass	
10501	60 Ltr.	Garagenfass	
10508	1 Ltr.	Dose	
Aral SuperTronic G SAE 0W-30		ACEA A3/B3, A3/B4 • API SL/ CF • MB 229.3/ 229.5 • VW 502 00/ 505 00 • BMW Longlife-01 • Fiat 9.55535-G1 • Opel GM-LL-A-025/ GM-LL-B-025	
10386	lose Ware		<p>Fully synthetic high performance engine oil for Mercedes-Benz, BMW- and GM-/Opel passenger cars.</p> <ul style="list-style-type: none"> • For diesel and gasoline engines • Reduces engine wear and provides peace of mind against breakdown • Can be used for extended oil change with flexible service intervals • Lower fuel and oil consumption
10380	205 Ltr.	Leihfass	
10381	60 Ltr.	Garagenfass	
10383	4 Ltr.	Kanister	
10382	1 Ltr.	Dose	
Aral SuperTronic LongLife III SAE 5W-30*		ACEA C3 • MB 229.51 • VW 504 00/ 507 00 (Fulfills technical requirements according to former VW approval 503 01) • BMW Longlife-04 • Porsche C30	
10476	lose Ware		<p>*Product available only within Europe, Technology only partially released globally.</p> <p>High performance engine oil based on latest technology for modern engines of the VW group** (VW, Audi, SEAT, Škoda).</p> <ul style="list-style-type: none"> • For gasoline and diesel engines • Reduces engine wear and provides peace of mind against breakdown • 'Aral Low SAPS-Technologie' maximizes diesel particle filter lifespan • For engines with and without LongLife service • Lower fuel consumption is environmentally beneficial <p>**except R5 and V10-TDI-Pump-Nozzle-engines in Phaeton, Touareg and T5 as well as certain Pump-Nozzle-Engines without LongLife service and without DPF. Consult User Manual.</p>
10470	205 Ltr.	Leihfass	
10471	60 Ltr.	Garagenfass	
10472	20 Ltr.	Kanister	
20479	4 Ltr.	Kanister	
20478	1 Ltr.	Dose	

Article No. Aral	Capacity	Container	
Engine Oils for Passenger Cars			
Aral HighTronic C SAE 5W-30		ACEA C1, Ford WSS-M2C934-B	
10586	lose Ware		<p>High performance engine oil with 'Aral Synthese Technologie'.</p> <ul style="list-style-type: none"> • Developed particularly for passenger cars with diesel particle filters requiring an ACEA C1 compliant engine oil • With Aral low SAPS-Technologie to help maximize life span of diesel particle filters
10582	205 Ltr.	Leihfass	
10589	1 Ltr.	Dose	
Aral HighTronic F SAE 5W-30		ACEA A1/B1, A5/B5 • API SL/ CF • Ford WSS-M2C913-A, WSS-M2C913-B, WSS-M2C913-C • ILSAC GF-4	
10336	lose Ware		<p>High performance engine oil with 'Aral Synthese Technologie' specially developed for passenger cars from Ford, Chrysler and Land Rover.</p> <ul style="list-style-type: none"> • For gasoline and diesel engines
10330	205 Ltr.	Leihfass	
10332	1 Ltr.	Dose	
Aral HighTronic G SAE 5W-30		ACEA C3 • API SM/ CF • Meets dexos2 performance level	
21386	lose Ware		<p>High performance engine oil with 'Aral Synthese Technologie'.</p> <ul style="list-style-type: none"> • dexos2 specially for all GM gasoline and diesel vehicles including diesel particulate filters developed 2010 onwards. • Modern low ash formulation with 'Aral Synthese Technologie' provides excellent wear protection • Protects engines against wear and deposit formation. Reduced wear can lead to reduced fuel consumption and can improve the efficiency of diesel particulate filters as well as the life expectancy of gasoline catalyst systems. • Meets ACEA 2007 A3/B3, A3/B4 performance levels
21380	208 Ltr.	Leihfass	
21381	60 Ltr.	Garagenfass	
21387	1 Ltr.	Dose	
Aral HighTronic J SAE 5W-30		ACEA C2 • PSA B71 2290	
20196	lose Ware		<p>High performance engine oil with 'Aral Synthese Technologie'.</p> <ul style="list-style-type: none"> • Developed specially for French and Japanese cars requiring an ACEA C2 compliant engine oil.
20190	208 Ltr.	Leihfass	
20191	60 Ltr.	Garagenfass	
20197	1 Ltr.	Dose	

Engine Oils

Passenger Cars



Article No. Aral	Capacity	Container	
Engine Oils for Passenger Cars			
Aral HighTronic M SAE 5W-30		ACEA A3/B3, A3/B4 • API SL/ CF • MB 229.3/ 229.5 • VW 502 00/ 505 00 • BMW Longlife-01 NEW	
21396	lose Ware		High performance engine oil with 'Aral Synthese Technologie' <ul style="list-style-type: none"> • High-Ash formulation with excellent additivation • For MB gasoline passenger cars and all passenger diesel engines without diesel particle filters • For gasoline and diesel engines from other car manufacturers, amongst them BMW and VW Group Will be replaced in Q4 2011 with Aral HighTronic M 5W-40 and deleted.
21390	208 Ltr.	Leihfass	
21391	60 Ltr.	Garagenfass	
21397	1 Ltr.	Dose	
Aral HighTronic R SAE 5W-30		ACEA C4 • Renault RN0720	
16006	lose Ware		High performance engine oil with 'Aral Synthese Technologie'. <ul style="list-style-type: none"> • Developed specially for modern Renault Turbo diesel engines with diesel particle filters.
16000	208 Ltr.	Leihfass	
16001	60 Ltr.	Garagenfass	
16007	1 Ltr.	Dose	
Aral HighTronic SAE 5W-40		ACEA C3 • API SL/ CF • MB 229.31 • VW 502 00/ 505 00/ 505 01 • Fiat 9.55535-S2 • Ford WSS-M2C917-A • Renault RN0700 / RN0710 • Porsche A40 NEW FORMULATION	
20636	lose Ware		High performance engine oil with 'Aral Synthese Technologie' for demanding driving conditions. <ul style="list-style-type: none"> • For gasoline and diesel engines, meets ACEA 2007 performance levels • Low SAPS Oil • To be used in VW Group Pump-Nozzle engines requiring a VW 505 01 specification • Exploits high performance reserves in engines with extended oil drain intervals and low top up requirements
20630	205 Ltr.	Leihfass	
20631	60 Ltr.	Garagenfass	
20633	20 Ltr.	Kanister	
20634	4 Ltr.	Kanister	
20637	1 Ltr.	Dose	
Aral HighTronic M SAE 5W-40		ACEA A3/B3, A3/B4 • API SN/ CF • MB 229.3/ 229.5 • VW 502 00/ 505 00 • BMW Longlife-01 • Renault RN0700 / 0710 • Porsche A40 NEW in Q4 2011	
tbc	lose Ware		High performance engine oil with 'Aral Synthese Technologie' <ul style="list-style-type: none"> • High-Ash formulation with excellent additivation • For MB gasoline passenger cars and all passenger diesel engines without diesel particle filters • For gasoline and diesel engines from other car manufacturers, amongst them BMW and VW Group Will replace Aral HighTronic M 5W-30 in Q4 2011.
tbc	208 Ltr.	Leihfass	
tbc	60 Ltr.	Garagenfass	
tbc	1 Ltr.	Dose	

Article No. Aral	Capacity	Container	
Engine Oils for Passenger Cars			
Aral BlueTronic SAE 10W-40		ACEA A3/B4 • API SL/ CF • MB 229.1 • VW 501 01/ 505 00	
20486	lose Ware		The engine oil with 'Aral Synthese Technologie'. <ul style="list-style-type: none"> • For gasoline and diesel engines.
10480	205 Ltr.	Leihfass	
10481	60 Ltr.	Garagenfass	
10487	20 Ltr.	Kanister	
20484	4 Ltr.	Kanister	
20488	1 Ltr.	Dose	
Aral Tronic SAE 15W-40		ACEA A2/B2 • API SH/ CG-4 • MB 229.1	
10496	lose Ware		Multifunctional engine oil based on mineral oil technology with good performance additivation. <ul style="list-style-type: none"> • For gasoline and diesel engines
10490	205 Ltr.	Leihfass	
10491	60 Ltr.	Garagenfass	
10492	20 Ltr.	Kanister	
10644	4 Ltr.	Kanister	
10647	1 Ltr.	Dose	



Article No. Aral	Capacity	Container	
Engine Oils for Heavy Trucks			
Aral SuperTurboral SAE 5W-30		ACEA E4, E7 • MB 228.5 • DAF HP-1/HP-2 • MAN M 3277 • MTU (Ölklasse 3) • Renault RXD • Scania LDF • Voith-Retarder Ölklasse B • Volvo VDS-2 • ZF TE-ML 07C	
11486	lose Ware		<p>Engine oil displaying superior performance with 'Aral Synthese Technologie' for latest generation trucks.</p> <ul style="list-style-type: none"> • Fuel savings of up to 4 % when compared to a standard 15W-40 engine oil as demonstrated in numerous fleet tests • For extended oil drain intervals of up to 150.000 km (please consult manufacturer handbook) • Optimized cold start properties • Excellent results in reducing deposits in turbo chargers and air intercoolers • Reduced wear to extend engine life • Excellent performance also in diesel fuels with high sulfur content <p>Must not be used in gasoline cars.</p>
11480	205 Ltr.	Leihfass	
11481	60 Ltr.	Garagenfass	
11482	20 Ltr.	Kanister	
11488	4 Ltr.	Kanister	
Aral SuperTurboral LA SAE 5W-30		ACEA E6, E7 • MB 228.51 • MAN M 3477 • Renault RLD-1 / RXD • Volvo VDS-3 NEW in Q3 2011	
tbc	lose Ware		<p>As of Q3 2011</p> <p>Aral SuperTurboral LA 5W-30 is a 5W-30 heavy duty diesel engine oil designed to allow fleet operators to run their new vehicles to extended oil drain intervals. Prime application is for latest low emission Euro 4 and Euro 5 European trucks and buses, specially those requiring a Low SAPS lubricant. It can also be used for older trucks and buses and in off-road vehicles and equipment that requires this performance level.</p> <ul style="list-style-type: none"> • Excellent low temperature characteristics ensure the oil is quickly circulated to all moving parts of the engine under cold start conditions. • Maintains the efficiency of exhaust after-treatment systems ensuring continued compliance with emissions legislation. • Designed to protect the latest European Vehicles against all types of engine wear, deposit and soot build-up and bore polishing. <p>Must not be used in gasoline cars.</p>
tbc	208 Ltr.	Leihfass	
tbc	20 Ltr.	Kanister	
tbc	4 Ltr.	Kanister	
Aral MegaTurboral LA SAE 10W-40		ACEA E6, E7 • MB 228.51/ 235.27 • MAN M 3477 • MTU (Ölklasse 3.1) • Renault RXD / RLD-2 • Voith-Retarder Ölklasse A • Volvo VDS-3	
13966	lose Ware		<p>Engine oil that conforms with strict Euro 4 and Euro 5 standards. Prevents deposits on major engine parts such as pistons and cams. Reduced Sulfur, Ash and Phosphorous content (Low SAPS Oil) makes this the right oil for Euro 4 and Euro 5. Maintains the efficiency of exhaust after-treatment systems ensuring continued compliance with emissions legislation.</p> <ul style="list-style-type: none"> • Designed to protect the latest European vehicles against all types of engine wear, deposit and soot build-up and bore polishing. The formulation continues to protect even under the most severe conditions thus extending engine life and preventing unscheduled downtime. • Enables longer drain intervals <p>Must not be used in gasoline cars.</p>
13960	205 Ltr.	Leihfass	
13962	20 Ltr.	Kanister	
13965	4 Ltr.	Kanister	

Article No. Aral	Capacity	Container	
Engine Oils for Heavy Trucks			
Aral MegaTurboral S SAE 10W-40		ACEA E7 • API CH-4 • Scania LDF-2 • Volvo VDS-3	
20136	lose Ware		<p>Modern high performance diesel engine oil that can be used for very long oil drain intervals provided manufacturer recommendations are checked.</p> <ul style="list-style-type: none"> • For trucks and busses of European manufacturers (particularly Scania) not needing a low SAPS oil • Can be used for older trucks, busses and off-road equipment assuming these need the specifications of the product <p>Must not be used in gasoline cars.</p>
20130	205 Ltr.	Leihfass	
Aral MegaTurboral SAE 10W-40		ACEA E4, E7 • API CF • MB 228.5 • MAN M 3277 • Renault RXD / RLD-2 • Voith-Retarder Ölklasse B • Volvo VDS-2	
13937	lose Ware		<p>Engine oil of superior performance with 'Aral Synthese Technologie' for current truck diesel engines capable of extended drain intervals. Fulfills both high demands of truck manufacturers and strict European engine test protocols.</p> <ul style="list-style-type: none"> • Reduces wear through a resistant oil film also in extreme temperatures and heavy loads • Optimized cold start properties • Excellent performance also in diesel fuels with high sulfur content • Capable of extended oil drain intervals up to 120.000 km (please consult manufacturer handbook) <p>Must not be used in gasoline cars.</p>
13930	205 Ltr.	Leihfass	
13931	60 Ltr.	Garagenfass	
13932	20 Ltr.	Kanister	
10625	5 Ltr.	Kanister	
Aral MegaTurboral VR SAE 10W-40		ACEA E9 • API CJ-4 • MB 228.31 • Caterpillar ECF-3 • Cummins CES 20081 • Mack EO-0 Premium Plus • MAN M 3275 • Renault RLD-3 • Volvo VDS-4 NEW in Q3 2011	
tbc	lose Ware		<p>As of Q3 2011</p> <p>Aral MegaTurboral VR 10W-40 is a multifunctional heavy duty diesel engine oil designed to allow fleet operators to run new 'global' low emission vehicles to extended oil drain intervals. It is a low SPAS oil specifically designed to meet the needs of the latest European and US industry and OEM specifications, on- and off-highway. Can be used especially for Volvo-, Renault-, Caterpillar- and Cummins engines in trucks where extended oil intervals are specified (please check manufacturers' manuals).</p> <ul style="list-style-type: none"> • Extended oil drain intervals to keep vehicles on the road for longer. The unique low SAPS additive system keeps on working even in the toughest conditions. • Minimises wear, protects engines and ensures prolonged engine life. <p>Must not be used in gasoline engines.</p>
tbc	208 Ltr.	Leihfass	
tbc	20 Ltr.	Kanister	

Engine Oils

Heavy Trucks



Article No. Aral	Capacity	Container	
Engine Oils for Heavy Trucks			
Aral ExtraTurboral SAE 10W-40		ACEA E7 • API CI-4/ SL • MB 228.3/ 229.1/ 235.28 • Caterpillar ECF-2 • Cummins CES 20076, CES 20077, CES 20078 • DAF HP-1/HP-2 • MAN M 3275 • MTU (Ölklasse 2) • Renault RLD • Voith Retarder Ölklasse B • Volvo VDS-2	
11166	lose Ware		<p>Engine oil with 'Aral Synthese Technologie' for mixed car parks with both diesel and gasoline cars.</p> <ul style="list-style-type: none"> • With powerful additivation providing fuel economy • Reduced inventory due to its versatility based on mixed fleet properties • Approved by car manufacturers for use at extended drain intervals • Prevents cold and black sludge <p>Must not be used in gasoline engines.</p>
11190	205 Ltr.	Leihfass	
11191	60 Ltr.	Garagenfass	
11182	20 Ltr.	Kanister	
21198	5 Ltr.	Kanister	
21197	1 Ltr.	Dose	
Aral PlusTurboral SAE 15W-40		ACEA E7 • API CI-4/ SJ • MB 228.3 • Caterpillar ECF-2 • Cummins CES 20076, CES 20077 • MAN M 3275 • Renault RLD • Volvo VDS-2	
11276	lose Ware		<p>Mineral oil based engine oil with excellent performance. Versatile formulation provides protection against wear and deposits, ensuring reduced maintenance costs and preventing unscheduled overtime.</p> <p>Must not be used in gasoline engines.</p>
11270	205 Ltr.	Leihfass	
11272	60 Ltr.	Garagenfass	
11281	20 Ltr.	Eimer	
21274	4 Ltr.	Kanister	
Aral MultiTurboral SAE 15W-40		ACEA E2 • API CG-4/ SH • MB 228.1/ 229.1 • MAN 271 • Volvo VDS	
11426	lose Ware		<p>Mineral oil based universal engine oil with very good performance for mixed car parks with both diesel and gasoline engines.</p> <ul style="list-style-type: none"> • Reduces many types of wear and will reduce the build-up of deposits • Approved for use at standard drain intervals • Meets ACEA 2008 A3/B3, A3/B4 performance levels.
11420	205 Ltr.	Leihfass	
11422	60 Ltr.	Eimer	
11438	20 Ltr.	Kanister	
11465	5 Ltr.	Kanister	
11468	1 Ltr.	Dose	
Aral BasicTurboral SAE 10W		API CF/ SF • MB 228.0 • Voith Retarder Ölklasse A	
11416	lose Ware		<p>Mineral oil based monograde engine oils with powerful additivation, may also be used as hydraulic oil. Can be used in hydraulic and transmission systems that specify use of a monograde engine oil. (please consult manufacturer handbook)</p>
11210	205 Ltr.	Leihfass	
11214	20 Ltr.	Kanister	
Aral BasicTurboral SAE 20W-20		API CF/ SF • MB 228.0 • Voith Retarder Ölklasse A	
11446	lose Ware		<p>Mineral oil based monograde engine oils with powerful additivation, may also be used as hydraulic oil. Can be used in hydraulic and transmission systems that specify use of a monograde engine oil. (please consult manufacturer handbook)</p>
11220	205 Ltr.	Leihfass	
11224	20 Ltr.	Kanister	

Article No. Aral	Capacity	Container	
Engine Oils for Heavy Trucks			
Aral BasicTurboral SAE 30		API CF/ SF • MB 228.0	
11476	lose Ware		<p>Mineral oil based monograde engine oils with powerful additivation, may also be used as hydraulic oil. Can be used in hydraulic and transmission systems that specify use of a monograde engine oil. (please consult manufacturer handbook)</p>
11230	205 Ltr.	Leihfass	
11237	20 Ltr.	Kanister	
Aral BasicTurboral SAE 40		API CF/ SF • MB 228.0	
11240	205 Ltr.	Leihfass	<p>Mineral oil based monograde engine oils with powerful additivation, may also be used as hydraulic oil. Can be used in hydraulic and transmission systems that specify use of a monograde engine oil. (please consult manufacturer handbook)</p>
11392	20 Ltr.	Kanister	
Aral BasicTurboral SAE 50		API CF/ SF • MB 228.0	
11250	205 Ltr.	Leihfass	<p>Mineral oil based monograde engine oils with powerful additivation, may also be used as hydraulic oil. Can be used in hydraulic and transmission systems that specify use of a monograde engine oil. (please consult manufacturer handbook)</p>
Aral Kowal CNG SAE 15W-40		MB 226.9 • DAF HP GAS • MAN M 3271-1 • Renault RGD • Volvo CNG	
61270	205 Ltr.	Leihfass	<p>High performance engine oil specially designed for gas fuelled engines sensitive to the formation of deposits on the piston crown, which lead to uncontrolled ignition, consequent loss of engine performance and if unchecked, complete engine failure.</p> <ul style="list-style-type: none"> • Contains advanced anti-wear additives to protect against premature engine failure from wear, so reducing maintenance costs
Aral SuperTraktoral SAE 10W-40		ACEA E2 • API CF-4/ CE/ SF/ GL-4 • John Deere JDM J27 • Massey Ferguson M1144, M1139 • ZF TE-ML 06C, 06D, 07B • Can be used where the following specification is required: Ford M2C-134D, M2C-159B • John Deere J20C • Massey Ferguson M1135	
11740	205 Ltr.	Leihfass	<p>Universal tractor oil with mineral oils.</p> <ul style="list-style-type: none"> • Provides excellent cold start protection which reduces engine wear • Meets the requirements of many agricultural manufacturers • Improved hydraulic response
11741	60 Ltr.	Garagenfass	
11743	20 Ltr.	Kanister	

Transmission Fluids

Passenger Cars and Trucks



Article No. Aral	Capacity	Container	
ATF			
Aral Getriebeöl SGF 84		MB 236.2	
15666	lose Ware		Automatic transmission fluid according to GM-Type A and other specifications according to manufacturers handbooks.
15670	205 Ltr.	Leihfass	
15677	20 Ltr.	Kanister	
Aral Getriebeöl ATF 22		MB 236.6 • MAN 339 Typ Z1/V1 • Voith 55.6335.3X • ZF TE-ML 03D, 04D, 11A, 14A, 17C	
15956	lose Ware		Automatic transmission fluid according to GM-specification ATF Typ II D. Recommended for use in automatic transmission and power steering systems.
15960	205 Ltr.	Leihfass	
15964	60 Ltr.	Garagenfass	
15972	20 Ltr.	Kanister	
15973	1 Ltr.	Dose	
15968	0,5 Ltr.	Dose	
Aral Getriebeöl ATF 55		MB 236.9 • MAN 339 Typ Z1/V1 • Voith 55.6335.3X • Volvo Transmission Oil 97341 • ZF TE-ML 04D, 14A, 17C	
15926	lose Ware		Transmission fluid for automatic transmissions according to previous GM-specification Dexron III F-30589. • Will improve low temperature gear shift and reduce component wear
15910	205 Ltr.	Leihfass	
15912	60 Ltr.	Garagenfass	
15922	20 Ltr.	Kanister	
15928	1 Ltr.	Dose	
Aral Getriebeöl ATF M 12		MB 236.12	
15946	lose Ware		Transmission fluid to be used in automatic passenger car transmissions according to current MB approval and GM specification with fuel economy potential.
15940	205 Ltr.	Leihfass	
Aral Getriebeöl ATF J		Daihatsu Alumix ATF Multi • Honda ATF Z-1 (not for CVT-Getriebe) • JASO M315 Type 1A • Mazda ATF D-III and ATF M-3 • Mitsubishi Diamond SP-II, SP-III • Nissan Matic Fluid C, D, J • Suzuki ATF Oil and ATF Oil Special • Toyota Type T, T-II, T-III, T-IV	
56636	lose Ware		Transmission fluid with 'Aral Synthese Technologie' to be used in automatic transmissions for a series of Asian passenger cars. • Fulfills and exceeds JASO 1A requirements for modern automatic transmissions according to manufacturer recommendations • Shows excellent oxidation and friction stability, combined with superb cold temperature performance • Ensures smooth and comfortable gear changes also in extreme temperatures
56630	205 Ltr.	Leihfass	
56633	20 Ltr.	Kanister	
56638	1 Ltr.	Dose	
Aral Getriebeöl ATF E-S		MB 236.8 • MAN 341 Typ Z2/V2 • Voith 55.6336.3X • ZF TE-ML, 04D, 09X, 14B, 16L	
15870	205 Ltr.	Leihfass	Fully synthetic automatic transmission fluid according to GM specification ATF Type II E. • Enables extended drain intervals for MB- and ZF-gearboxes

Article No. Aral	Capacity	Container	
ATF			
Aral Getriebeöl ATF LD		MB 236.81 • MAN 339 TYP Z3/V2 • Voith H55.6336.3X • ZF TE-ML 04D, 11B, 14C, 16M	
20150	205 Ltr.	Leihfass	Fully synthetic automatic transmission fluid designed for use at maximum oil drain intervals in buses and coaches with automatic or semi-automatic transmissions. Its formulation is free from chlorine and heavy metals for reduced environmental impact. • With excellent thermal and oxidative stability, combined with unique shear stability, will give extended drain capability and reduce service costs • With outstanding cold flow properties combined with excellent extreme pressure and anti-wear additives that ensure the transmission is protected at all times especially at start-up
20153	20 Ltr.	Kanister	
Manual			
Aral Getriebeöl EP SAE 80W		API GL-4 • MB 235.1 • MAN 341 Typ Z1/E1 • ZF TE-ML 02A, 17A	
15056	lose Ware		Standard transmission fluid for manual gear boxes and axles requiring an oil approved against API GL-4.
15080	205 Ltr.	Leihfass	
15084	60 Ltr.	Garagenfass	
15113	20 Ltr.	Kanister	
15089	0,5 Ltr.	Flasche	
Aral Getriebeöl EP SAE 85W-90		API GL-4 • MB 235.1 • MAN 341 Typ Z1/E1 • ZF TE-ML 02A, 16A, 17A, 19A	
15126	lose Ware		Multifunctional transmission fluid for manual gear boxes and axles requiring an oil approved against API GL-4.
15090	205 Ltr.	Leihfass	
15094	60 Ltr.	Garagenfass	
15103	20 Ltr.	Kanister	
15108	1 Ltr.	Dose	
Aral Getriebeöl EP SAE 85W-140		API GL-4	
15074	20 Ltr.	Kanister	Multifunctional transmission fluid for manual gear boxes and axles requiring an oil approved against API GL-4.
Aral Getriebeöl EP SYNTH SAE 75W-90		API GL-4 + • VW 501 50 (G50)	
15476	lose Ware		High performance gear oil in with 'Aral Synthese Technologie'. Can be used for multiple applications in passenger cars, 2-stroke-gearboxes as well as construction or agricultural transmissions.
15470	205 Ltr.	Leihfass	
15474	60 Ltr.	Garagenfass	
15462	20 Ltr.	Kanister	
15468	1 Ltr.	Dose	

Transmission Fluids

Passenger Cars and Trucks



Article No. Aral	Capacity	Container	
Manual			
Aral Getriebeöl SNS SAE 75W-80		API GL-4 • MAN 341 Typ Z3/E3 • ZF TE-ML 02D	
26356	lose Ware		Part-synthetic transmission fluid for use in manual transmissions as well as those equipped with or without interlockers, mechanical non-synchronized transmissions, steering systems and supplementary transmissions. <ul style="list-style-type: none"> • Excellent synchroniser performance and balanced frictional characteristics improving shift comfort and functionality and improving fuel economy over conventional gear lubricants • Exceptional temperature reduction through reduced friction gives longer oil and component life
26350	205 Ltr.	Leihfass	
26352	20 Ltr.	Kanister	
Aral Getriebeöl SNS-A SAE 75W-85		API GL-4 • MB 235.4 • MAN 341 TYP E4 • Volvo Transmission Oil 97307	
20180	205 Ltr.	Leihfass	Fully synthetic high performance manual transmission fluid recommended for most commercial vehicle manual transmissions (truck, bus, light commercial vehicle) where API GL4 lubricants are required. <ul style="list-style-type: none"> • Provides excellent synchroniser performance and balanced frictional characteristics to improve shift comfort and functionality and improve fuel economy over conventional gear lubricants
20183	20 Ltr.	Kanister	
Aral Getriebeöl SNS-B SAE 75W-80		API GL-4 • MAN 341 Typ E4/VR • Voith Retarder Ölklasse C	
26396	lose Ware		Fully synthetic high performance transmission fluid for vehicle gearboxes, steering boxes and axles. <ul style="list-style-type: none"> • To be used for oil drain intervals up to 400.000 km (please follow manufacturer recommendations)
26394	205 Ltr.	Leihfass	
26392	20 Ltr.	Kanister	
Aral Getriebeöl SNS-AT SAE 75W-90		API GL-4 • MB 235.11	
20140	205 Ltr.	Leihfass	Specifically for use in the manual transmissions of Mercedes Benz Actros vehicles. <ul style="list-style-type: none"> • Excellent synchroniser performance which improves shift ability, reducing the 'hard' gear changing, often experienced in commercial vehicles • Very good cold flow properties which provide smoother gear shift at low ambient temperatures due to reduced shifting forces • Reduced torque loss increases efficiency over all transmission load ranges • Increased wear protection of synchroniser and bearings during start-up phase
20143	20 Ltr.	Kanister	
Aral Fluid HGS SAE 80W		API GL-4 • Case MS 1207, MS 1209 • MF M1145, M1143, M1135 (Service) • Volvo WB 101 • ZF TE-ML 03E, 05F, 17E	
15176	lose Ware		Combined hydraulic and transmission fluid. <ul style="list-style-type: none"> • Can be used in modern commercial vehicles where a single lubricant for hydraulic system, brakes and gear box is recommended
15180	205 Ltr.	Leihfass	
15181	60 Ltr.	Garagenfass	
15187	20 Ltr.	Kanister	

Article No. Aral	Capacity	Container	
Manual			
Aral Fluid T0-4 SAE 10W		Allison C4 • Cat Lastschaltgetriebeöl (TDTO) • Komatsu • ZF TE-ML 03C	
15200	205 Ltr.	Leihfass	Transmission fluid universally applicable for construction and agricultural vehicles.
Aral Fluid T0-4 SAE 30		Allison C4 • Cat Lastschaltgetriebeöl (TDTO) • Komatsu • ZF TE-ML 03C, 07F	
15226	lose Ware		Transmission fluid universally applicable for construction and agricultural vehicles.
15190	205 Ltr.	Leihfass	
Aral Fluid T0-4 SAE 50		Cat Lastschaltgetriebeöl (TDTO) • Komatsu	
15236	lose Ware		Transmission fluid universally applicable for construction and agricultural vehicles.
15210	205 Ltr.	Leihfass	
Axle			
Aral Getriebeöl HYP LS SAE 85W-90		API GL-5 • ZF TE-ML 05C, 12C, 16E, 21C	
14406	lose Ware		Mineral oil based extreme pressure gear lubricant designed to cope with the special friction characteristics of limited slip differentials and associated hypoid gears. It has been developed particularly for use in limited slip rear axles fitted to high performance cars.
14410	205 Ltr.	Leihfass	
14412	20 Ltr.	Kanister	
Aral Getriebeöl HYP SAE 80W		API GL-5 • MAN 342 Typ M1 • ZF TE-ML 17B	
14246	lose Ware		Recommended for use in the final drives of most vehicles and in some manual transmissions where API GL5 lubricants are required. It is not suitable for limited slip applications. (please follow manufacturer recommendations)
14280	205 Ltr.	Leihfass	
14242	20 Ltr.	Kanister	
Aral Getriebeöl HYP SAE 85W-90		API GL-5 • MB 235.0 • MAN 342 Typ M1 • ZF TE-ML 05A, 16C, 17B, 19B, 21A	
14256	lose Ware		Recommended for use in the final drives of most vehicles and in some manual transmissions where API GL5 lubricants are required. It is not suitable for limited slip applications.
14290	205 Ltr.	Leihfass	
14294	60 Ltr.	Garagenfass	
14303	20 Ltr.	Kanister	
14257	1 Ltr.	Dose	
Aral Getriebeöl HYP SAE 85W-140		API GL-5 • ZF TE-ML 05A, 16D, 21A	
14276	lose Ware		Recommended for use in the final drives of most vehicles and in some manual transmissions where API GL5 lubricants are required. It is not suitable for limited slip applications.
14270	205 Ltr.	Leihfass	
14232	20 Ltr.	Kanister	

Transmission Fluids

Passenger Cars and Trucks



Article No. Aral	Capacity	Container	
Axle			
Aral Getriebeöl SNA-D SAE 80W-90		API GL-5 • MB 235.20 • MAN 342 M3 • Scania STO 1:0 • ZF TE-ML 05A, 12E, 16B, 17B, 19B, 21A	
26410	205 Ltr.	Leihfass	Specifically designed for use in hypoid, bevel and spiral gear units, axles and final drives operating under severe conditions and over a wide range of operating temperatures. <ul style="list-style-type: none"> The product characteristics enable it to meet the requirements of several automotive manufacturers for cars, vans and commercial trucks, buses or agricultural machines Should only be used for synchronized manual gearboxes if lubricants of API GL-5 performance level are explicitly recommended for such units
Aral Getriebeöl HYP SYNTH SAE 75W-90		API GL-5	
14376	lose Ware		High performance transmission fluid with 'Aral Synthese Technologie'. <ul style="list-style-type: none"> Multifunctional SAE 75W-90 for hypoid units and axles For heavy load transmissions both in passenger cars and commercial vehicles
14370	205 Ltr.	Leihfass	
14374	60 Ltr.	Garagenfass	
14377	20 Ltr.	Kanister	
Aral Getriebeöl BS SAE 75W-90		API GL-5 • MAN 342 Typ S1 • Scania STO 1:0 • ZF TE-ML 05B, 12B, 17B, 19C, 21B	
26326	lose Ware		Fully synthetic transmission fluid, specially designed and fully approved by BMW for use in all BMW final drives fitted with conventional (non limited slip) differentials. Should be used for BMW final drives fitted with limited slip differentials. Fully approved for MAN 342 for back axles.
26320	205 Ltr.	Leihfass	
Aral Getriebeöl BS-LSX SAE 75W-140		API GL-5 • MB 235.61 • MAN 342 M2 • ZF TE-ML 05D, 12D, 16G, 18, 21D	
26340	205 Ltr.	Leihfass	A fully synthetic SAE 75W-140 hypoid gear oil formulated for use in both conventional and limited slip differentials. <ul style="list-style-type: none"> Whilst being suitable for all applications where a lubricant of this quality is specified, it is specially formulated for use in limited slip differentials fitted to Japanese vehicles requiring an SAE 75W-140 Extreme Pressure Gear Oil. Has additionally demonstrated outstanding performance in competition vehicles employing limited slip differentials. Is also specifically designed for BMW differentials including the Z3 limited slip differential.
26344	50 Ltr.	Garagenfass	
26342	20 Ltr.	Kanister	
Aral Getriebeöl SNA-C SAE 75W-90		API GL-5 • MB 235.8 • MAN 342 Typ S1 • Scania STO 1:0 • Volvo Transmission Oil 97312 (new) • ZF TE-ML 05B, 07A, 12B, 16F, 17B NEW SPECIFICATION	
26406	lose Ware		Fully synthetic high performance transmission fluid for axles and manual transmissions for service intervals up to 400,000 km (please consult manufacturer handbook).
26404	205 Ltr.	Leihfass	
26402	20 Ltr.	Kanister	

Article No. Aral	Capacity	Container	
Manual and Axle			
Aral Getriebeöl EP Plus SAE 80W-90		API GL-4/ GL-5/ MT-1 • MAN 3343 Typ M • ZF TE-ML 02B, 05A, 12E, 16B, 17B, 19B, 21A	
15446	lose Ware		Designed for use in all types of automotive gear units, axles and final drives, including hypoid and synchronized transmissions. <ul style="list-style-type: none"> Is formulated to pass extreme-pressure tests required for highly loaded hypoid axle and synchromesh specifications for modern manual gearboxes Was originally developed for commercial vehicles, but is suitable also for passenger cars, agricultural and construction equipment
15450	205 Ltr.	Leihfass	
15454	60 Ltr.	Garagenfass	
15452	20 Ltr.	Kanister	
Aral Getriebeöl SNA-B SAE 80W-140		API GL-5 • Scania STO 1:0 / Schaltgetriebe + Hinterachse	
26366	lose Ware		High performance gear oil with 'Aral Synthese Technologie' for rear axles and gear boxes according to OEM recommendations. To be used primarily for heavy duty vehicles across a wide temperature range, for example with Renault and DAF. Has been developed for extended drain intervals up to 400 000 km. Can be used for Scania gearboxes as well as axles.
26360	205 Ltr.	Leihfass	
Aral Getriebeöl SNA-E SAE 75W-90		API GL-1/ GL-5 • MB 235.8 • MAN M 3343 Typ S, 341 Typ E3 • Scania STO 1:0 (for axles) • ZF TE-ML 02B, 05B, 12B, 16F, 17B, 19C, 21B	
20120	205 Ltr.	Leihfass	Fully synthetic, multi-purpose heavy duty automotive gear lubricant for use in complete driveline applications requiring either API GL-4 or GL-5 performance. <ul style="list-style-type: none"> Provides the relatively high viscosity and load carrying characteristics necessary for heavy duty drive axles and transfer cases Fully compatible with conventional mineral oil based products, but its superior oxidative/thermal stability gives the potential for extended drain As an SAE 75W-90 grade, its low temperature flow properties deliver fuel economy benefits while its viscosity/temperature characteristics are suitable for year round use Recommended for service fill and top-up of commercial vehicles, construction equipment and passenger car manual transmissions, transfer cases and drive axles in DAF, Scania, Volvo, Eaton, Iveco and RVI equipment
20123	20 Ltr.	Kanister	
Aral Getriebeöl HYP SC SAE 85W-140		API GL-5/ MT-1 • Scania STO 1:0 (for axles) • ZF TE-ML 05A, 12E, 16D, 21A	
20090	205 Ltr.	Leihfass	A generic transmission fluid exceeding API classifications GL4 and GL5.
20093	20 Ltr.	Kanister	

Article No. Aral	Capacity	Container	
Antifreeze			
Aral Antifreeze Silikatfrei		MB 325.3 • VW, Audi, Seat, Škoda (VW TL 774D = G12+) • ASTM D 4985, ASTM D 3306 • DAF • Ford WSS-M97B44-D • MAN 324 Typ SNF • Opel • Renault (Typ D)	
<p>A nitrite, phosphate, amine and silicate-free coolant containing ethylene glycol. It has been developed to meet the growing demand from manufacturers for a higher performance coolant based on organic acid technology (OAT).</p> <ul style="list-style-type: none"> • Aqueous solutions act as both an antifreeze and coolant and impart very good anti-corrosion protection to all metal parts found in the cooling systems especially for latest full aluminum engines 			
Aral Antifreeze Extra		MB 325.0 • VW, Audi, Seat, Škoda (VW TL 774C = G11) • BMW • ASTM D 4985-89, ASTM D 330 • BS 6580 • BWB • Deutz • Liebherr • MAN 324 Typ NF • MTU • Opel • Rover • Saab • Volvo • Porsche	
<p>Balanced formulation of mono ethylene glycol and corrosion inhibitors. A nitrite, phosphate and amine-free coolant containing ethylene glycol. It has been developed to meet the growing demand from manufacturers for a higher performance coolant that minimises environmental impact.</p> <ul style="list-style-type: none"> • Aqueous solutions act as both an antifreeze and coolant and impart very good anti-corrosion protection to all metal parts found in the cooling systems especially for latest full aluminum engines 			
Brakefluids			
Aral Bremsflüssigkeit HS DOT 4		FMVSS 116, DOT 4 • ISO 4925 • SAE S 1704	
16732	60 Ltr.	Garagenfass	
16733	0,5 Ltr.	Dose	
<p>A high performance, synthetic brake fluid which exceeds the requirements of the SAE J1703, FMVSS116 DOT 3 and DOT 4, ISO 4925 and JIS K2233 specifications.</p> <ul style="list-style-type: none"> • Formulated from mixed polyalkylene glycol ethers together with carefully selected additives. These enable the fluid to operate at a high performance level throughout its service life, offering system protection together with ultimate braking confidence. • Specially formulated to meet the demanding requirements of modern, high performance, automotive brake and clutch systems with the exception of those for which a mineral oil based fluid is specified 			
Aral Bremsflüssigkeit HS DOT 4 Super		FMVSS 116, DOT 4 (DOT 4+, DOT 4 Super) • ISO 4925 • SAE J 1703	
16752	60 Ltr.	Garagenfass	
<p>A high boiling synthetic brake fluid which far exceeds the requirements of the SAE J1703, FMVSS 116 DOT 3 and 4, ISO 4925 and JIS K2233 specifications. Designed for use in all brake systems particularly those which are exposed to extreme conditions. This product has been formulated from mixed polyalkylene glycol ethers and borate ester together with other high performance additives and inhibitors which give ultimate system protection against the effects of corrosion and high temperature vapour lock.</p> <p>Specifically designed to be a high temperature alternative to DOT 5.1 fluids. Its superior characteristics give added benefit in situations where extreme conditions are encountered and ultimate braking response required. Based on glycol ether and borate ester technology and as such has a high vapour lock point (measurement relating to high temperature performance under braking conditions). Because of the nature of this formulation, the vapour lock point can be sustained at a higher level than conventional glycol ether based fluids during the service life of the product. Should not be used in braking systems for which a mineral oil based fluid is recommended.</p>			
Additional products			
Aral Kipper-Hydrauliköl		MB 341.0 • DIN 51524 T2 Typ HLP • ISO VG 15	
17000	205 Ltr.	Leihfass	Special hydraulic fluid.
17002	20 Ltr.	Kanister	
Aral LHM +		PSA B 712710	
17017	1 Ltr.	Dose	Mineral based fluid specifically for Citroen hydraulic systems with green reservoirs. Specifically designed for use in powered hydraulic systems. Fully compatible with all elastomers used in existing automotive powered hydraulic systems recommending this fluid type. High viscosity index (VI) with unique viscometric properties.

Article No. Aral	Capacity	Container	
Greases			
Aral Mehrzweckfett		MB 267.0 • K2K-30	
18100	180 kg	Fett drum	<p>A smooth lithium based grease.</p> <ul style="list-style-type: none"> • Universal grease for wide applications for passenger cars and trucks • Contains hydroxystearate soaps which combine properties of good low temperature pumpability, good resistance to mechanical shear, ability to operate at moderately high temperatures and excellent water and corrosion resistance
18101	50 kg	Hob.	
18113	18 kg	Eimer	
18105	5 kg	Eimer	
18119	0,4 kg	Kartusche	
Aral Mehrzweckfett F		Caterpillar • Ford • KPF2K-30	
18604	18 kg	Eimer	<p>Water resistant lithium based grease containing molybdenum disulphide (MoS₂).</p> <ul style="list-style-type: none"> • High load carrying capacity • Reduced wear in heavy and shock loaded conditions, reducing machine downtime for repairs and maintenance • Prevents scuffing and fretting. Good oxidation stability, water resistance and corrosion protection
18608	0,4 kg	Kartusche	
Aral Langzeitfett H		MB 267.0 • K2K-20	
18710	180 kg	Fett drum	<p>A smooth lithium based grease with extreme pressure (EP) additives.</p> <ul style="list-style-type: none"> • Universal grease for wide applications for passenger cars and trucks • Good oxidation stability, water resistance and corrosion protection
18711	50 kg	Hob.	
18713	18 kg	Eimer	
18718	0,4 kg	Kartusche	
Aral Radlagerfett		KP 2 N-30 • MAN 284 Li-H2	
18323	18 kg	Eimer	<p>High performance lithium complex grease for use in ball or roller bearings operating at high speeds, high loads and high temperatures.</p> <ul style="list-style-type: none"> • Excellent thermal stability and wide operating temperature • High load carrying capacity • Good water resistance and adhesion to metal surfaces
Aral Fließfett N		MB 264.0 • GP 00 K-40 • Lincoln • Vogel	
18803	18 kg	Eimer	<p>A lithium soap semi-fluid (NLGI 00) grease for centralized lubrication systems of trucks, buses and off-highway equipment.</p> <ul style="list-style-type: none"> • Wide operating temperature range • Excellent load carrying capabilities. Good resistance to water, giving excellent corrosion protection.

Last Update: Mai 2011

The content of this brochure corresponded to surrender to the state of the art.
The right to change specifications and application notes are reserved.

Aral Aktiengesellschaft
Geschäftsbereich Schmierstoffe
Max-Born-Str. 2
22761 Hamburg

www.aral-lubricants.com